In the claims:

Si tion to market a mark

::12

1 12 =

1. In a radio communication system having a mobile station operable to
communicate by way of a first network pursuant to a first-network communication service
subscription, the first network operable pursuant to a first communication-standard protocol and
the first network coupled to a second network, the second network operable pursuant to a second
communication standard protocol, an improvement of apparatus for facilitating invocation of a
second-network service, resident at a second-network service control point, by the mobile
station, said apparatus comprising:

a bridge mechanism coupled to receive a first-network-generated request for invocation of the second-network service by the mobile station, said bridge mechanism at least for selectably initiating authorization of the mobile station to involve the second-network service.

- 2. The apparatus of claim 1 wherein the first network comprises a legacy network, wherein the second network comprises a new network and the second-network service comprises a new-network service, the new network service unavailable at the legacy network, and wherein the request to which said bridge mechanism is coupled to receive comprises a first communication-standard protocol message.
- 3. The apparatus of claim 1 wherein said bridge mechanism comprises a first communication-standard protocol message detector, said first communication-standard protocol message detector for detecting the first communication-standard protocol message that requests the invocation of the second-network service.

2

3

4

1

2

3

4

[,] 4

2

4

111 1.5

ı n k 6

7

1

2

3

- The apparatus of claim 3 wherein said bridge mechanism further comprises a 4. second communication-standard, protocol-request message generator for generating a second communication standard protocol-request message for communication to the second-network service control point to request invocation of the second-network service by the mobile station.
 - 5. The apparatus of claim 4 wherein said bridge mechanism further comprises a second communication-standard, protocol-response message detector for detecting a second communication-standard protocol-response message generated by the second-network service control point and returned to said bridge mechanism.
 - The apparatus of claim 5 wherein said bridge mechanism further comprises a first 6. communication standard, protocol-response message generator coupled to receive indications of detection by said second communication-standard, protocol-response message detector of the second communication-standard protocol-response message, said first communication-standard protocol-response message generator for generating a first communication standard-protocol response message indicative of a value of the second communication-standard protocol response message.
- The apparatus of claim 1 wherein said bridge mechanism comprises a first 7. functional part functionally operable pursuant to the first communication-standard protocol and a second functional part functionally operable pursuant to the second communication-standard protocol.

2

3

4

1

2

3

1 11 2

4

1,4

ıak 2

3

4

5

6

- 8. The apparatus of claim 7 wherein the radio communication station comprises a cellular communication system, wherein the first network is constructed pursuant to a communication standard that defines a media gateway and wherein the first functional part comprises media gateway functionality.
- 9. The apparatus of claim 8 wherein the second network is constructed pursuant to a communication standard that defines a softswitch and wherein the second functional part comprises softswitch functionality.
- The apparatus of claim 9 wherein the second-network service comprises a prepaid calling service and wherein the request for the invocation of the second-network service to which said bridge mechanism is coupled to receive comprises a request for the invocation of the prepaid calling service.
- 11. The apparatus of claim 9 wherein the first network comprises a registry at which service-subscription information associated with the mobile station is stored, the servicesubscription information including an indication of association of the mobile station with the second-network service, and wherein the request for invocation of the second-network service to which said bridge mechanism is provided thereto subsequent to access to the service-subscription information stored at the registry.
- 12. The apparatus of claim 11 wherein the request for the invocation of the secondnetwork service is detected by the first functional part of said bridge mechanism. 2

- 1 13. The apparatus of claim 12 wherein the authorization selectably initiated by said 2 bridge mechanism is provided by the second functional part of said bridge mechanism.
- 1 14. The apparatus of claim 13 wherein the authorization selectably initiated by the
- 2 second functional part of said bridge mechanism comprises a second-communication-standard
- 3 protocol-formatted request routable by the second functional part to the second-network service
- 4 control point.



1	15. In a method for communicating in a radio communication system having a mobile
2	station operable to communicate by way of a first network pursuant to a first-network
3	communication service subscription, the first network operable pursuant to a first
4	communication-standard protocol and the first network coupled to a second network, the second
5	network operable pursuant to a second communication-standard protocol, an improvement of a
6	method for facilitating invocation of a second-network service, resident at a second-network
7	service control point, by the mobile station, said method comprising:
8	generating a first-communication-standard protocol message at the first network
.9	to request invocation of the second-network service by the mobile station; and
(1) 10 (1)	generating a second-communication-standard protocol message responsive to the
11	first-communication-station standard protocol message generated during said operation of
11	generating the first-communication-standard protocol message, the second-communication-
13	standard protocol message generated at the second network and representative of the request for
14 14 11	the invocation of the second-network service by the mobile station.
1	16. The method of claim 15 comprising the further operations of:
2	routing the second-communication-standard protocol message to the second-
3	network service control point; and
4	selectably granting the request for the invocation of the second-network service
5	subsequent to delivery of the second-communication-standard protocol message to the second-
6	network service control point.

2

- 1 The method of claim 16 comprising the further operation of:
- 2 generating a grant message at the second-network service control point, the grant
- 3 message formatted pursuant to the second communication standard protocol.
- 1 18. The method of claim 17 comprising the further operation of:
- 2 converting the grant message into a second-communication-standard protocol-
- 3 formatted message.
 - 19. The method of claim 18 wherein the first network comprises a legacy network and the second network comprises a new network, wherein the second-network service comprises a new-network service unavailable at the legacy network, and wherein the first-communication-standard protocol message generated during said operation of generating the first-communication-standard protocol message requests invocation of the new-network service by the mobile station operable pursuant to the legacy network.
 - 20. The method of claim 16 wherein the first-communication-standard message is provided to a bridge mechanism bridging the first network and the second network, and wherein the second-communication-standard protocol message is generated by the bridge mechanism.